


TC-518

Professional

Two-Way Radio

HYT's TC-518 is ideal for hotels and other businesses that need secure and dependable communications in a compact and professional design. This radio's volume control, single-hand operation, and voice operated transmit capability make it very user-friendly and convenient for users that may have their hands occupied at different times during the work day.







- Stylish, Compact, & Light Weight
- User-Friendly Volume Control & Single-Hand Operation
- Wide-Band Coverage
- Battery Save & Low Battery Alert
- Voice Operated Transmit (VOX) w/ Applicable Accessories



TC-51 **Professional Two-way Radio**

Technical Highlights -

■ Wide-Band Coverage

Covers a wider range of frequencies allowing the radio to be more compatible.

■ User-Friendly Volume Adjustment

The easily maneuverable volume control is divided into levels with an audible tone identifying each level

Single-Hand Operation

Enabled by the combined design of the PTT and Volume Control.

■ Sleek & Light-Weight

With its ergonomic design, this slim and compact radio can enhance user comfort, while maintaining a professional and fashionable appearance.

■ Built-in Voice Scrambler/Compander

Only compatible with the HYT TC-320 & TC-518 radio models.

■ Voice Operated Transmit (VOX)

Hands-free transmit is possible, when paired with an applicable accessory.

Main Features-

- High / Low Power Switchable
- Battery Save & Low Battery Alert
- Programmable Channel Spacing (Wide / Narrow Band Selectable)
- Busy Channel Lockout
- Time-out Timer
- CTCSS / CDCSS Encode & Decode
- Squelch Tail Elimination
- Selectable Squelch Level (0-9)
- **Channel Scan**
- PC Programmable
- Wired Clone
- Power Off by Software

General ———

Frequency Range (MHz)	VHF: 136-174 UHF: 350-390*; 400-470; 470-520
Channel Capacity	16
Channel Spacing (KHz)	25/12.5**
Operating Voltage (V)	7.4
RF Power Output (W)	5W/2W (VHF) 4W/2W (UHF)
Battery	1100 mAh (Li-lon)
Battery Life (5-5-90 duty cycle)	About 9 Hours
Frequency Stability (ppm)	± 2.5
Operating Temperature (F°)	-22° ~ +140° (F°)
Antenna Impedance (Ω)	50
Dimensions	4.33 in. x 2.05 in. x 1.10 in.
Weight (with antenna & battery)	8.46 oz.

^{*}Frequencies Marked with an Asterisk(*) are for Export Only.

All specifications are tested according to TIA/EIA-603, and subject to change without notice due to continuous development. More detailed specs available upon request.

Recommended Applications -

- Hotels
- Hospitals
- Supermarkets
- Education

- Property Management
- Retail Stores
- Restaurants
- Office Environments









Accessories

Standard Accessories

Li-lon Battery (1100mAh) BL1102 Rapid-rate Charger (for Li-lon Battery) CH10L12 Switching Power (different P/N for different countries and areas) Belt Clip BC12 Strap RO03

Featured Optional Accessories







The Six-unit Switching Power works with chargers



Highlights: Using the 6-unit switching power, you can combine multiple rapid-rate chargers as a simple multi-unit charger which fulfills high-speed shift or busywork for large fleets, and share the economical benefits and convenience that it brings.















Your Local Dealer

FCC Approved Bands: (400-470MHz) FCC ID Number R74TC-518U1









HYT America, Inc.

320 International Parkway, Sunrise, Florida 33325 Tel: 800-845-1230 Fax: 954-846-1672

Web: http://www.hytamerica.com

SHENZHEN HYT SCIENCE & TECHNOLOGY CO., LTD.

#YT is the registered trademark of Shenzhen HYT Science & Technology Co., Ltd. © 2009 HYT, Co., Ltd. All Rights Reserved.

HYT retains the right to change the product design and specifications. Should any printing mistake occur, HYT will not bear relevant

^{**}Below 5KHz Channel Spacing Not Possible.